



Sunshine Coast and Hinterland

Phone : (07) 5491 6934

Mobile: 0408 917 934

[info@coastalautosystems.com.au](mailto:info@coastalautosystems.com.au)



Mobile service

## Heavy Duty multi camera system.

- 7" High Performance TFT LCD Monitor
- Brightness of 400cd/m<sup>3</sup>
- Up to 4 camera inputs
- Multiple split picture displays (1, 2, 3 or 4 cameras)
- 2 video outputs to enable recording
- Adjustable mirror function for individual cameras
- Distance gauge for reverse view
- Allows DVD or video input
- Auto reverse function
- Auto split screen on indicator activation
- NTSC or PAL compatible
- Auto day and night brightness control
- 12/24 volt compatible



Mobile service

## 9" Industrial Quad Monitor with DVR Function

9-inch digital quad monitor with video recording function;

Recording file stored in SD CARD

Maximum 32G -12 hours continuous recording

support 720x240(NTSC)/720x288(PAL) 30fps

Video file layout: AVI; Coded format: motion JPEG

Touch screen: 9 inch resistive touch screen

Support touch button control function

Support IR remote control

System format: NTSC/PAL

Support four cameras inputs

Image display mode: single, dual, triplex, quad, PIP

Five trigger lines:

Operating voltage range: 10-32V

Short-circuit protection function



Phone : (07) 5491 6934  
Mobile: 0408 917 934

[info@coastalautosystems.com.au](mailto:info@coastalautosystems.com.au)



**Bracket Camera with Infra Red  
CCD**  
With Audio and IR  
PAL / NTSC  
Effective Pixels: 512 x 582 pixels / 512 x 492 pixels  
Sensing Area: 4.9mm x 3.7mm  
Resolution: 420TV lines  
0 Lux/F1.2 with IR  
White Balance: Auto  
Shutter: 1/60(NTSC) / 1/50(PAL) ~ 1/10,000 Seconds  
Current Consumption: Max. 300mA  
Power Supply: DC12V  
Operating Temperature: -20°C~70°C , RH95% MAX  
Storage Temperature: -40°C~80°C,RH95% MAX  
Lens Angle: 130°

Mobile service



Mobile service

**Ball Camera  
CCD**  
Effective Pixels: 512 x 582 pixels / 512 x 492 pixels  
Resolution: 420TV lines  
0Lux (Infrared lamps on) 0 .1Lux(day) / F1.2  
White Balance: Auto  
Shutter: 1/60(NTSC) / 1/50(PAL) ~ 1/10,000 Seconds  
BLC: Auto  
Current Consumption: Max. 150mA  
Power Supply: DC12V  
Operating Temperature: -20°C~70°C , RH95% MAX  
Storage Temperature: -40°C~80°C,RH95% MAX

**Pricing varies with each machine combination**  
Price on request for each vehicle combination.  
Starting at similar prices to Motor Home systems

**Truck and Industrial Cameras**  
[info@coastalautosystems.com.au](mailto:info@coastalautosystems.com.au)